# Specifications



Photo is representative





## Eaton 9E3000I

Eaton 9E UPS, 3000 VA, 2400W, Input: C20, Output: (6) C13, (1) C19, Tower

| General specifications | |
|---|---|
| **PRODUCT NAME** | Eaton 9E UPS |
| **CATALOG NUMBER** | 9E3000I |
| **UPC** | 786689166588 |
| **PRODUCT LENGTH/DEPTH** | 19 cm |
| **PRODUCT HEIGHT** | 33 cm |
| **PRODUCT WIDTH** | 39.9 cm |
| **PRODUCT WEIGHT** | 24.2 kg |
| **COMPLIANCES** | CE Marked<br>TUV |
| **CERTIFICATIONS** | IEC/EN 62040-1<br>IEC/EN 62040-2<br>CE<br>EAC |

Powering Business Worldwide

## Additional information

| | |
|---|---|
| **AUTO SHUTDOWN FUNCTION** | Yes |
| **COLOR** | Black |
| **CONSTRUCTION TYPE** | Free standing model |
| **EFFICIENCY AT MAX. LOAD** | 91 |
| **HOT SWAP POWER** | No |
| **INTERNAL BYPASS** | Yes |
| **PACKAGE CONTENTS** | • UPS<br>• USB cable<br>• Serial cable<br>• Quickstart guide<br>• Safety instructions |
| **PHASE (INPUT)** | 1 |
| **PHASE (OUTPUT)** | 1 |
| **RACK MOUNTING KIT** | No |

## Battery specifications

| | |
|---|---|
| **BATTERY MANAGEMENT** | • Automatic battery test<br>• Deep discharge protection |
| **BATTERY QUANTITY** | 6 |
| **BATTERY RATING** | 12 V / 9 Ah |
| **BATTERY REPLACEMENT** | Replacable batteries |
| **BATTERY TYPE** | Sealed, lead-acid |
| **EXTENDED BATTERY CAPABILITY** | Yes |
| **RUNTIME GRAPH** | View runtime graph |

## Communication

| | |
|---|---|
| **COMMUNICATION** | • USB port (HID compliant)<br>• Serial port (RS232)<br>• Communication slot |
| **ETHERNET INTERFACE** | No |
| **EXPANSION SLOTS** | One slot for optional communication card |
| **INCLUDES NETWORK CARD** | No |
| **POTENTIAL FREE SWITCH CONTACT** | No |
| **SOFTWARE COMPATIBILITY** | Eaton Intelligent Power Manager, Eaton Intelligent Power Protector |
| **TYPE OF INTERFACE** | Other |
| **USER INTERFACE** | LCD Display |

## Electrical input

| | |
|---|---|
| **INPUT CONNECTION** | C20 |
| **INPUT FREQUENCY RANGE** | 40-70 Hz |
| **INPUT NOMINAL VOLTAGE** | 230V default (220/230/240V) |
| **INPUT POWER FACTOR** | >.99 |
| **INPUT VOLTAGE RANGE** | 176-300 V (100 V-300 V with derating) |
| **NOMINAL FREQUENCY** | 50/60 Hz |

## Electrical output

| | |
|---|---|
| **FEED TYPE** | 1 |
| **OUTPUT NOMINAL VOLTAGE** | 230V default (220/230/240V) |
| **OUTPUT POWER FACTOR** | 0.8 |
| **OUTPUT VOLTAGE RANGE** | 220/230/240 V +/- 2% |
| **OUTPUT WAVEFORM** | Sine wave |
| **RECEPTACLE** | (6) C13, (1) C19 |
| **TOPOLOGY** | Online/Double-conversion |
| **VA RATING** | 3000 VA |
| **VOLTAGE** | 230V |
| **VOLTAGE DISTORTION OUTPUT (LINEAR LOAD) - MAX** | 3 |
| **WATTAGE** | 2400 W |

## Environmental

| | |
|---|---|
| **ALTITUDE** | 3000 m |
| **NOISE LEVEL** | <37 dB at 1 meter |
| **RELATIVE HUMIDITY** | 0-95% non-condensing |
| **TEMPERATURE RANGE** | 0° to 40°C (32° to 104°F) |

## Resources

| | |
|---|---|
| DECLARATIONS OF CONFORMITY | EU Declaration of Conformity |
| MANUALS AND USER GUIDES | Eaton 9E 1kVA-3kVA UPS<br>Eaton 9E EBM - Advance user guide |
| TECHNICAL DATA SHEETS | Eaton 9E UPS - Datasheet<br>Eaton 9E Rack_Datasheets |

| | |
|---|---|
| **PROJECT NAME:** | |
| **PROJECT NUMBER:** | |
| **PREPARED BY:** | |
| **DATE:** | |

**Eaton Corporation plc** Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.